

VICTORY[®]

ULTRASPEC

PROJECT: _____

ITEM # _____ QTY: _____

MODEL # _____

AIA # _____ SIS # _____

SELF-CONTAINED BLAST CHILLER/SHOCK REACH-IN FREEZER

VBCF12-100PU

SELF-CONTAINED BLAST CHILLER/SHOCK REACH-IN FREEZER



CABINET CONSTRUCTION

- Stainless Steel Exterior And Interior
- Die-Formed Interior Floor Has Rounded Corners
- Central Drain For Easy Cleaning
- Anti-Condensation Perimeter Heating Around Door Opening
- Ergonomic Vertical Door Handle And Stainless Steel
- Snap In Place Magnetic Gaskets Self Closing Door With Hold Open Stop At 100°

FEATURES

- Soft And Hard, Timed Or Core Probe Blast Chilling
- Soft And Hard, Timed Or Core Probe Shock Freezing
- Automatic Recognition Of Core Probe
- Multi Point Sensor Temperature Display Button
- Core Probe Heater Button
- HACCP Alarm Display Button
- Pre-Cooling Cycle Button
- Adjustable Evaporator Fan Speed Button
- Timed Manual Defrost Button
- USB Data Recorder/Interface
- Infinity Mode Program With Adjustable Set Point
- Automatic Conservation Mode At End Of Cycle
- On Board Recipe Book With 68 Pre-Set Programs
- 99 Free Memory Positions For Custom Programs
- LCD Illuminated Temperature Display
- Unit Comes Standard With Twelve (12) Wire Rod Tray Slides
- Real Time Clock
- One, High Precision Heated Multi Sensor Probe
- Stainless Steel Feet

REFRIGERATION

- Self-Contained Refrigeration System Uses R290 Refrigerant
- Evaporator Fitted With A High Flow Rate Fan Insures Maximum Cooling Efficiency
- Indirect Air Flow Assures Highest Product Quality
- Manual Defrosting With Door Open On A Timed Cycle
- Blast Chilling (194°F to 37°F in 90 minutes) Or Shock Freezing (194°F to 0°F in 240 minutes) Cycles



- ▶ 3 Year Parts & Labor Warranty
- ▶ Plus An Additional 2 Year Compressor Warranty
- ▶ Exclusive 2 Year Warranty On Magnetic Door Gaskets



Please Verify Qualifying Units By Visiting:
www.energystar.gov/cfs

OPTIONS & ACCESSORIES

- UV Sterilization Lamp (must be added at time of order)
- Change Door Swing
- Single Sensor Probes (up to 4 possible)
- Casters With Brakes


3779 Champion Blvd, Winston-Salem, NC 27105

ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com | VictoryRefrigeration.com

Rev. 1/24/23 Printed in U.S.A.

APPROVAL: _____ DATE: _____



We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

CHARACTERISTICS		REFRIGERATION DATA		SHIPPING DETAILS	
Width, Overall (in.)	33.46"	Condensing Unit Size, HP	2.0	Height	78"
Depth, Overall (with handle) (in)	39.37"	Refrigerant	R290	Width	38"
Height Overall (in.)	71.26"	Capacity (BTU/HR) (113°F/-13°F)	7,208	Depth	37"
Width, Door Open 90° (in)	69.76"	Capacity (BTU/HR) (104°F/14°F)	15,252	Crated Weight	602 lbs
Door Opening (in.)	28.74" x 36.61"	Refrigerant Amount (lbs)	3.53	* Pans Not Included	
Wall Thickness (in)	2.36"	PAN COUNT & PERFORMANCE			
Number of Doors	1	Sheet Pan Capacity* (18" x 26")	12		
ELECTRICAL DATA		Steam Table Pan Capacity* (12" x 20")	12		
Cabinet Voltage	208-240/60/3	Chilling Capacity In 90 Min	100 lbs		
Total Amperes	9.0	Freezing Capacity In 240 Min	70 lbs		
NEMA Plug	15-20P	Climate Class	5		

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com | VictoryRefrigeration.com

Rev. 1/24/23 Printed in U.S.A.

an Ali Group Company



The Spirit of Excellence